

Product Name: REBEL Crazy Horse (Brown)  
 Product Description: REBEL Platinum Range  
 Product Code: RE652

# REBEL

## AFRICA'S HARDEST WORKING BOOTS

## SAFETY GEAR



### Materials

CE EN ISO 20345:2011-S1



<p><b>Upper</b> Full Grain Crazy Horse Leather</p> <p><b>Footbed</b> Extra Thick Anti-Static Footbed with Poron Padding</p> <p><b>Inner Sole</b> Biagioli IBITECH 252 2mm Foam Insole Board</p> <p><b>Lining</b> Breathable and Abrasion Resistant Tai-brelle (Equivalent to Cambrelle)</p>	<p><b>Toe Cap</b> Steel Toe Cap - Tested to 200J</p> <p><b>Toe Guard</b> TPU Anti-scutt Toe Guard</p> <p><b>Sole</b> Dual Density PU/Rubber Heat-Resistant Sole</p>
---	---

### Specifications

<b>Specifications</b>	<ul style="list-style-type: none"> <li>ISO European Norm EN20345-S1, HRO</li> <li>Tested by INTERTEK - Approved Body Identification Number : 0362</li> </ul>
<b>Special Features</b>	<ul style="list-style-type: none"> <li>Sole resistant to 300°C (degrees Celsius)</li> </ul>
<b>Sole</b>	<ul style="list-style-type: none"> <li>Temperature Maximum 300°C (degrees Celsius)</li> <li>Oil and acid resistant PU/Rubber</li> <li>Slip Resistance - Tested to SATRA PM144 1992 and meets these requirements However, care should always be taken on wet or oily surfaces</li> <li>Crack Resistance - Tested to 30,000 flex cycles</li> </ul>
<b>Toe Cap</b>	<ul style="list-style-type: none"> <li>Tested to an impact resistance of 200 Joules</li> </ul>
<b>Anti Static Properties</b>	<ul style="list-style-type: none"> <li>Product is anti static. If application is life critical additional consultation with product expert is required. Electrical resistance can be significantly changed by flexing, contamination or moisture. Introduction of additional inner sole reduces static resistance</li> </ul>
<b>Sizing</b>	<ul style="list-style-type: none"> <li>Available from Size 4 to Size 13 (Unisex)</li> </ul>
<b>Lifespan</b>	<ul style="list-style-type: none"> <li>The application determines the length of service that should be achieved. Normal environments should provide 12 months' service, if appropriate care is taken. Refer Care guidelines</li> </ul>

### Uses

### Suitability

### Comments

<p>General</p> <p>Construction</p> <p>Mining</p> <p>Petrochemical</p> <p>Engineering</p> <p>Power Generation</p> <p>Agriculture</p> <p>Food &amp; Health</p> <p>Fishing &amp; Allied Industries</p> <p>Fabrication</p> <p>Metal Industries</p> <p>Motor Industry</p> <p>Glass Manufacturing &amp; Fabrication</p> <p>Municipality</p> <p>Waste Disposal</p> <p>Civil Contracting</p> <p>Moving and Rigging</p> <p>Forestry</p> <p>Telecommunications</p> <p>Contract Labour</p> <p>Transport - Air, Road &amp; Rail</p> <p>Transport - Shipping</p>	<p>Widely used</p> <p>Highly suitable</p> <p>Highly suitable</p> <p>Widely used</p> <p>Highly suitable</p> <p>Highly suitable</p> <p>Not Required</p> <p>Not Required</p> <p>Not Required</p> <p>Widely used</p> <p>Highly suitable</p> <p>Widely used</p> <p>Widely used</p> <p>Not Required</p> <p>Not Required</p> <p>Widely used</p> <p>Widely used</p> <p>Not Required</p> <p>Not Required</p> <p>Widely used</p> <p>Not Required</p> <p>Not Required</p>	<p>Care in very wet areas required. Gumboots would be more suitable for wet area applications</p> <p>Steel midsole advised to protect against glass penetration of the sole - (Ref: RE608-S3, RE210-S3, RE424, RE425, FX2-S1P)</p>
---	--	--

It is important that the footwear selected must be suitable for the protection required by the wearer and the environment. If any uncertainty exists consultation between buyer and seller should be conducted to ensure that the correct footwear is selected. This application guide only offers very general advice and should be confirmed if there may be any concerns over potential protection from hazards of any form.

To view the complete REBEL Safetygear range, please visit: [www.rebelsafetygear.com](http://www.rebelsafetygear.com)